



- Platform access from ground
- Full-pressure, open-centre hydraulic system
- Tool circuit at platform of twin buckets
- Side by side boom design giving lower centre of gravity
- Emergency stop valves at all upper and lower control stations with patented boom linkage
- Secondary stowage system
- Engine start/stop
- Dual controls on twin basket option to meet new ANSI
- Lower boom stow protection

A robust heavy duty design for increased versatility and maneuverability for maintenance work.

The Altec AM50 features an added material handling package. Also, with the jib and winch fitted, the bucket capacity is not reduced, as with other makes. The Altec AM50 can be easily mounted onto a 16t GVW chassis. This 2-man platform has 90° hydraulic platform rotation on twin-bucket option and 2x 181kg platform capacity.

FEATURES

- Insulating; ANSI 92.2 Category C and EN61057
- Altec ISO-Grip® control system (U.S. Patent No. 7,416,053)
- 4-function, single handle upper control dielectrically tested to 40kV AC with no more than 400 microamperes of leakage. (The control handle is green in colour to differentiate it from other non-tested controllers)
- Fiberglass lower boom and telescopic inner boom
- Fiberglass single 2-man platform, 24" x 48" x 42" or twin single-man baskets
- Altec ARM jib capacities up to 907kg

OPTIONS

- Twin basket option
- Emergency pump run function on engagement of PTO
- Strong arm jib removal lift and storage system
- Set of spreaderfeet
- Different stabiliser styles
- Many others on request

